

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/109942 A1

(51) International Patent Classification⁷: H04B 1/38, 1/14

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/IB2003/002174

(22) International Filing Date: 10 June 2003 (10.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEINONEN, Marko [FI/FI]; Rantapellontie 1C9, FIN-90520 Oulu (FI). ROUSU, Seppo [FI/FI]; Sahankuja 1, FIN-90800 Oulu (FI).


(74) Agent: COHAUSZ & FLORACK (24); Bleichstrasse 14, 40211 Düsseldorf (DE).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVING THE PERFORMANCE OF A RECEIVER IN INTERFERING CONDITIONS



WO 2004/109942 A1

(57) Abstract: The invention relates to a device (20) comprising a receiver (21) for receiving and processing signals at least in a first frequency band and an antenna (216) which is connected to the receiver (21). In order to improve the performance of such a receiver, the device (20) comprises in addition a tuning component (217) for shifting a frequency response of the antenna (216) from the first frequency band to a second frequency band. Further, the device (20) comprises a controlling portion (221) causing the tuning component (217) to shift the frequency response of the antenna (216) from the first frequency band to the second frequency band, in case a wideband noise is expected in the first frequency band. The invention relates equally to a corresponding method.